

V7 R1911

Value Line

Specifications

Panel Size	19" (~ 483 mm)	
Aspect Ratio	5:4 (~ 376 x 301 mm)	
Panel Specification	HannStar Panel TN	
Recommended Resolution	1280 x 1024	
Pixel Pitch	0.294 mm	
Colours max.	16.2 Mio	
Brightness typ.	300 cd/m²	
Contrast Ratio typ.	700:1	
Viewing Angle H/V	150° / 135°	
Response Time typ.	5 ms	
Features	speakers, Kensington® security port, internal power supply, silver-black design	
Frequency at Resolution	640 x 480	@ 75 Hz
	800 x 600	@ 75 Hz
	1024 x 768	@ 75 Hz
	1280 x 1024	@ 75 Hz
Horizontal Frequency	30 - 80 kHz	
Vertical Frequency	56 - 75 Hz	
Videobandwidth	135 Mhz	
Input Signal	RGB Analog	
Input Terminal	15pin D-Sub	
Plug & Play	VESA DDC 1/2B	
Power Management	VESA, DPMS, EPa, NUTEK	
Power Consumption On/Off	42/1 Watt max.	
Power Requirements	AC 100 - 240V, 50/60 Hz	
Operating/Storage Temperature	5° - 40° / -20° - 60°	
Operating/Storage Humidity	20 - 80% / 10 - 90% (no condensation)	
Dimensions WxHxD		
with stand	419 x 439 x 200 mm	
packaging	565 x 500 x 123 mm	
Weight with stand	4.7 kg	
incl. packaging	5.8 kg	
Tilt	-3° ~ 17°	
Wallmountable	VESA 100 x 100 mm	
Certifications & Standards	CE, TUV/GS, FCC, UL, TCO'03, ISO 13406-2, Energy Star	
Supplied Accessories	multilingual user manual CD, warranty card, quick installation guide, power cable, VGA cable, audio cable	
Pixel Criteria	bright <= 3, dark <= 3, total <= 7	
Service	3 years on-site	

